

DIGICODE 704-2

HI-RESOLUTION TUBE CONVERTOR 192 KHz / 24 Bit / 3 selectable digital inputs



The new Digicode 704-2 digital tube D to A converter is based on PCM-1794 , high-resolution dac, output circuits is design around vacuum tube type miniwatt without any solid state components from dac-ic to output !

Audio spdif digital signals accepted up to 192 kHz 24-bit on all inputs.

The digital inputs are :

- ⇒ Spdif IEC-958 as RCA 75 ohm connector @ resolution 192 KHz 24 bit
- ⇒ Spdif IEC-958 as BNC 75 ohm connector @ resolution 192 KHz 24 bit
- ⇒ AES-EBU AES-3 as XLR 110 ohm connector @ resolution 192 KHz 24 bit

Analog output :

- ⇒ Unbalanced output as 2.5 volt 250 ohm
- ⇒ Real balanced output as 2.5 volt 250 ohm x 2

Performances :

Input selector [3 digital inputs] by sequential single shot by push button, led indicator for selected input.
Led indicator for analog and digital supply
Led lock indicator for spdif / aes-ebu input
Separate power supply unit model PSU-DGC with digital and analog section selectable
Available as two option: lateral cherry wood panels or black solid plexiglas panels

Technical details :

2 x dac BB PCM 1794
Digital spdif receiver as Lector proprietary circuits SPDIF reconstruction signal for perfect wave and very low residual jitter
4 x tubes double triode output as ECC-81/ 12AT7 premium grade selected for real balance output
Hi grade tickness 1.5 mm chassis with special damping processing painting
Three mode suspension feets : soft rubber / alluminium spikes / iso footers [available from Lector audio strumenti]
Lector Digidrive TL-3 is a perfect companion for absolute hi-quality CD-Player system



hand-made in Italy by:
Lector strumenti audio
Via Verdi,35 27010 Albuzzano PV-ITALY EEC-
tel: 0382.484165 fax: 0382.481021
E-mail: info@lector-audio.com
web: <http://www.lector-audio.com>

